

# FLD Series

LED FLOOD ULTRA THIN



<b>Part #</b>	UT-FLD-150W-50K
<b>Project</b>	
<b>Type</b>	

U Technology's FLD is a mixed-use LED Flood lighting system perfect for high ceiling applications. The fixtures have a Lumen output of over 18,000 and are IP65 rated for protection from dust and moisture. With a powder-coated die cast aluminum construction and carefully designed LED technology, the FLD lights are exceptionally durable, highly-efficient, and extremely long lasting.



## PRODUCT SPECIFICATIONS:

<b>Input Voltage</b>	120V AC 50/60Hz	<b>Projected Lifespan</b>	+50,000 hours
<b>Power Consumption</b>	150W	<b>Dimensions</b>	L: 14"   W: 9.5"   D: 1.6"
<b>Lumen Output</b>	18,000 (± 10%)	<b>Weight</b>	6.6lbs
<b>Temperature</b>	-40°C to +55°C	<b>Power Factor</b>	+93%
<b>Construction</b>	Die-cast Aluminum Tempered Glass	<b>CCT</b>	5000K
<b>Installation</b>	Surface mount	<b>Rating</b>	Wet location (IP65)
<b>Beam Angle</b>	120°	<b>Certification</b>	cUL to CSA Standards
		<b>Warranty</b>	5 years

## ORDERING INFORMATION:

<b>Part #:</b>
UT-FLD-150W-50K

