



Engineered Lighting Solutions

LLW Series

COMMERCIAL LINEAR LED WRAP FIXTURES



SPECIFICATION




0-10V DIMMING



SURFACE



SUSPENSION



SWITCHABLE CCT

LLW SERIES - 4 FT

LINEAR LED WRAP FIXTURES | COMMERCIAL / ARCHITECTURAL



Part #	UT-LLW-4FT-36W-
Project	
Type	



U Technology's LLW Wrap fixtures are the perfect solution for general area lighting in numerous commercial and multi-unit residential applications. The install options are surface mount or suspension by aircraft cables. These fixtures are suitable in schools, hospitals, airports, hospitality, and multi-level parkades. The LLW is easy to install, covers 120-277V AC input voltages and is dimmable to suit different applications.

PRODUCT SPECIFICATIONS:

Input Voltage	120V-277V AC
Power Consumption	36W
Delivered Lumens	Up to 4,600 Lm
Beam Angle	160°
Dimming	0-10V
Switchable CCT	3000K, 3500K, 4000K
Construction	White trim, steel housing, polycarbonate lens
Installation	Surface mount - horizontal or vertical

Rating	Damp location
Dimensions (L x W x H)	49.21" x 4.55" x 3.58"
Certification	cUL to CSA Standards
Warranty	5 years*
Expected Life	50,000 hrs
Temperature Rating	-30°C to 40°C
Accessories	SK: Suspension kit** MS: Motion sensor EB: Emergency battery backup DA: DALI driver

* Must meet U Technology Terms and Conditions


** Standard suspension kit: 24" min to 60" max

ORDERING INFORMATION:

Part #	CCT		
UT-LLW-4FT-36W-	30K	35K	40K



DIMMING



SWITCHABLE CCT

ACCESSORY SELECTION:

Suspension Kit	Motion Sensor	Emergency Battery Backup	DALI Driver
SK	MS	EB	DA



SURFACE



SUSPENSION

LLW SERIES - 2 FT* SPECIAL ORDER ONLY

LINEAR LED WRAP FIXTURES | COMMERCIAL / ARCHITECTURAL



Part #	UT-LLW-2FT-18W-
Project	
Type	



U Technology's LLW Wrap fixtures are the perfect solution for general area lighting in numerous commercial and multi-unit residential applications. The install options are surface mount or suspension by aircraft cables. These fixtures are suitable in schools, hospitals, airports, hospitality, and multi-level parkades. The LLW is easy to install, covers 120-277V AC input voltages and is dimmable to suit different applications.

PRODUCT SPECIFICATIONS:

Input Voltage	120V-277V AC
Power Consumption	18W
Delivered Lumens	Up to 2,300 Lm
Beam Angle	160°
Dimming	0-10V
Switchable CCT	3000K, 3500K, 4000K
Construction	White trim, steel housing, polycarbonate lens
Installation	Surface mount - horizontal or vertical

Rating	Damp location
Dimensions (L x W x H)	20.20" x 4.55" x 3.58"
Certification	cUL to CSA Standards
Warranty	5 years*
Expected Life	50,000 hrs
Temperature Rating	-30°C to 40°C
Accessories	SK: Suspension kit** MS: Motion sensor EB: Emergency battery backup DA: DALI driver

* Must meet U Technology Terms and Conditions


** Standard suspension kit: 24" min to 60" max

ORDERING INFORMATION:

Part #	CCT		
	30K	35K	40K
UT-LLW-2FT-18W-			



DIMMING



SWITCHABLE CCT

ACCESSORY SELECTION:

Suspension Kit	Motion Sensor	Emergency Battery Backup	DALI Driver
SK	MS	EB	DA



SURFACE



SUSPENSION

LLW SERIES - 8 FT* SPECIAL ORDER ONLY

LINEAR LED WRAP FIXTURES | COMMERCIAL / ARCHITECTURAL



Part #	UT-LLW-8FT-65W-
Project	
Type	



U Technology's LLW Wrap fixtures are the perfect solution for general area lighting in numerous commercial and multi-unit residential applications. The install options are surface mount or suspension by aircraft cables. These fixtures are suitable in schools, hospitals, airports, hospitality, and multi-level parkades. The LLW is easy to install, covers 120-277V AC input voltages and is dimmable to suit different applications.

PRODUCT SPECIFICATIONS:

Input Voltage	120V-277V AC
Power Consumption	65W
Delivered Lumens	Up to 8,000 Lm
Beam Angle	160°
Dimming	0-10V
Switchable CCT	3000K, 3500K, 4000K
Construction	White trim, steel housing, polycarbonate lens
Installation	Surface mount - horizontal or vertical

Rating	Damp location
Dimensions (L x W x H)	97.60" x 4.55" x 3.58"
Certification	cUL to CSA Standards
Warranty	5 years*
Expected Life	50,000 hrs
Temperature Rating	-30°C to 40°C
Accessories	SK: Suspension kit** MS: Motion sensor EB: Emergency battery backup DA: DALI driver

* Must meet U Technology Terms and Conditions

** Standard suspension kit: 24" min to 60" max

ORDERING INFORMATION:

Part #	CCT		
	30K	35K	40K
UT-LLW-8FT-65W-			



DIMMING



SWITCHABLE CCT

ACCESSORY SELECTION:

Suspension Kit	Motion Sensor	Emergency Battery Backup	DALI Driver
SK	MS	EB	DA



SURFACE



SUSPENSION