



LED CYLINDER FIXTURES

SURFACE MOUNT



by  UTechnology

Engineered Lighting Solutions



LED CYLINDER FIXTURES - SURFACE

Surface Mount LED Cylinder Fixtures with Endless Versatility

Introducing the Rhythm Elite LED Cylinder Fixtures. Engineered to combine beautiful and powerful lighting with the flexibility of surface mounted cylindrical fixture lighting. The complete Rhythm Elite family of products includes cylinder fixtures and a track head system with matching form factors, power and light output for smooth and consistent lighting throughout any commercial space. Also available in Pendant Mount.

Why choose the Rhythm Elite family of products?

- A complete engineered solution for your lighting projects
- Designed with ultra low-glare Total Internal Reflection (TIR) optics
- Up to 192 different product configurations for endless versatility
- Complimentary Track Lighting System is available




ARCHITECTURAL




DIMMING



HIGH CRI



2 TRIM OPTIONS



4 CCT OPTIONS




QUICKSHIP

Please inquire about our Quickship Program




RHYTHM ELITE

LED CYLINDER FIXTURES - SURFACE | ARCHITECTURAL | SPECIFICATIONS




PRODUCT DIMENSIONS:

All dimensions are approximate, please acquire a sample of the product for exact sizing.



D1: 4-1/2"

APERATURE



D2: 2-3/8"

Power Consumption	15W	20W	30W
Input Voltage	120-277VAC*	120-277VAC*	120-277VAC*
Delivered Lumens	1,350 Lm ± 10%	1,800 Lm ± 10%	2,700 Lm ± 10%
Dimensions (inches)	D1: 4-1/2 x H: 5-4/5		
Aperture Size (inches)	D2: 2-3/8		

* Consult with U Technology for 347V option

GENERAL SPECIFICATIONS:

Dimming	0-10V*
CCT	2700K 3000K 3500K 4000K
Finish	Black White
CRI	+90 R9 +55
Beam Angles	15° 25° 40° 60°
Rating	IP20
Construction	Aluminum


Optics Technology	Total Internal Reflection (TIR)
Temperature Rating	-30°C to +40°C
Warranty	5 years**
Certification	cETL Listed to CSA Standards, ETL, CE, FCC, RoHS, LM70 >110,000 hrs
Mounting	Standard 4" octagonal junction box

* Consult with U Technology for other dimming options

** Must meet U Technology's Terms and Conditions

RHYTHM ELITE

LED CYLINDER FIXTURES - SURFACE | ARCHITECTURAL | ORDER FORM



Project Name:					
Quantity:				Type:	
Part #: UT-RCS-	1	2	3	4	5

1 POWER:	15W: 1,350 Lm	20W: 1,800 Lm	30W: 2,700 Lm		
2 BEAM ANGLE:	15D: 15°	25D: 25°	40D: 40°	60D: 60°	
3 CCT:	27K: 2700K	30K: 3000K	35K: 3500K	40K: 4000K	
4 FINISH COLOR:	BK: Black	WH: White			
5 IP RATING:	IP20: Dry Location				
ACCESSORIES: Quantity of additional interchangeable TIR optics	15°	25°	40°	60°	